



## SPECIFICATION SHEET

### Gaboon BS1088 Marine Grade Plywood

Gaboon (Okoume) Plywood is a strong but lighter weight plywood for general marine applications.

Description	Gaboon Light Marine Grade Plywood of Multi Ply construction.
Specie	Faces of 1mm Okoume and core of 100% Okoume veneer
Panel Size	2440x1220mm
Colouring	Pale pink to pale brown.
Overall Thickness	6mm, 9mm, 12mm, 15mm, 18mm, 22mm & 25mm. Tolerance +/-0.5mm. Additional 1.5mm and 3mm but not to BS1088.
Pack sizes	(Per 40' HC FCL) 4mm/250, 6mm/170, 9mm/100, 12mm/80, 15mm/65, 18mm/58, 22mm/50
Texture	Even, medium texture, smooth semi-lustrous surface.
Source	Manufactured in China with materials sourced from North West Africa where reforestation and sustainable yield forestry practices are being developed.
Grade	A/A
Glue	WBP Resorcinol (A Bond) 72 Hour Boil test.
Weight	530kg/m3 Strength F8
Screwing	Good screw holding through multi ply construction.

**Durability** Moderately durable. Factory tested for water and heat resistance. However it must be noted that exterior grade marine plywood panels are not required to be naturally durable and thorough sealing with preservative compounds, paints or resins is normal trade practice and necessary for exterior or marine applications.

**Uses** Most applications where a lighter panel weight is beneficial, such as head linings, cabinetry, bulkheads etc. Excellent substrate for decorative wood veneer or laminate overlay. Can be clear coated, so wall panels, shop fitting or any other application where a quality manufactured and light weight panel has benefits.

#### **Panel Systems International Ltd**

P O Box 935  
Whangaparaoa 0943  
New Zealand

Phone +64 9 4243219  
Mobile +64 21 801746  
Email [kerry.pearson@panelsystemsinternational.com](mailto:kerry.pearson@panelsystemsinternational.com)  
[www.panelsystemsinternational.com](http://www.panelsystemsinternational.com)