



## SPECIFICATION SHEET

### PSI B/B Grade Plywood

A general purpose exterior grade plywood with smooth paintable faces that can be branded to your own brand (Laser Branding). Quality manufacture with very few core gaps and no core overlaps.

Description	PSI B/B Grade Plywood of Multi Ply construction.
Specie	Faces of Okoume and core of mixed light hardwood veneers
Panel Size	2440x1220mm
Colouring	Pale pink to pale brown, with core mid brown.
Overall Thickness	4mm - 30mm. Tolerance +/- 0.5mm
Texture	Even, medium texture, smooth semi-lustrous surface.
Source	Manufactured in China with materials sourced from North West Africa and Europe where reforestation and sustainable yield forestry practices are being developed.
Grade	B/B
Glue	WBP Resorcinol (A Bond) for core and Melamine 48 hr 72 Hour between faces and core.
Weight	620kg/m <sup>3</sup>
Screwing	Good screw holding through multi ply construction.
Strength	F8
Durability	Moderately durable. Factory tested for water and heat resistance. However it must be noted that exterior grade marine plywood panels are not required to be naturally durable and thorough sealing with preservative compounds, paints or resins is normal trade practice and necessary for exterior applications.
Uses	A general purpose plywood for cabinetry, bulkheads etc. Excellent substrate for decorative wood veneer or laminate overlay. Can be clear coated, so wall panels, shop fitting or any other application where an economic and paintable surface is preferable. All home handyman applications etc.

#### **Panel Systems International Ltd**

P O Box 935  
Whangaparaoa 0943  
New Zealand

Phone +64 9 4243219  
Mobile +64 21 801746  
Email [kerry.pearson@panelsystemsinternational.com](mailto:kerry.pearson@panelsystemsinternational.com)  
[www.panelsystemsinternational.com](http://www.panelsystemsinternational.com)